

Außengerät		RXJ25A5V1B	
Innengerät		FTXJ25A2V1BW	
Function		Heating season	
Kühlung	Ja	Average (mandatory)	Ja
Heizen	Ja	Warmer (if designated)	Ja
		Colder (if designated)	Nein
Element	Symbol	Wert	Gerät
Design Load			
Kühlung	P _{designc}	2.50	kW
heating / Average	P _{designh}	2.45	kW
heating / Warmer	P _{designh}	1.32	kW
heating / Colder	P _{designh}		kW
Deklarierte Leistung* für Kühlen, bei Innentemperatur 27 (19) °C und Außentemperatur Tj		Deklarierte Leistung* für Kühlen, bei Innentemperatur 27 (19) °C und Außentemperatur Tj	
Tj = 35 °C	P _{dc}	2.50	kW
Tj = 30 °C	P _{dc}	1.85	kW
Tj = 25 °C	P _{dc}	1.22	kW
Ti = 20 °C	P _{dc}	1.19	kW
Declared capacity* for heating / Average season , at indoor temperature 20 °C and outdoor temperature Tj		Declared coefficient of performances* / Average season, at indoor temperature 20 °C and outdoor temperature Tj	
Tj = -7 °C	P _{dh}	2.17	kW
Tj = 2 °C	P _{dh}	1.32	kW
Tj = 7 °C	P _{dh}	0.93	kW
Tj = 12 °C	P _{dh}	1.13	kW
Tj = Bivalent temperature	P _{dh}	2.17	kW
Ti = operating limit	P _{dh}	2.07	kW
Declared capacity* for heating / Warmer season , at indoor temperature 20 °C and outdoor temperature Tj		Declared coefficient of performance* / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj	
Tj = 2 °C	P _{dh}	1.32	kW
Tj = 7 °C	P _{dh}	0.93	kW
Tj = 12 °C	P _{dh}	1.13	kW
Tj = Bivalent temperature	P _{dh}	1.32	kW
Ti = operating limit	P _{dh}	1.32	kW
Declared capacity* for heating / Colder season , at indoor temperature 20 °C and outdoor temperature Tj		Declared coefficient of performance* / Colder season, at indoor temperature 20 °C and outdoor temperature Tj	
Tj = -7 °C	P _{dh}		kW
Tj = 2 °C	P _{dh}		kW
Tj = 7 °C	P _{dh}		kW
Tj = 12 °C	P _{dh}		kW
Tj = Bivalent temperature	P _{dh}		kW
Tj = operating limit	P _{dh}		kW
Ti = -15 °C	P _{dh}		kW
Bivalent temperature		operating limit	
heating / Average	T _{biv}	-7	°C
heating / Warmer	T _{biv}	2	°C
heating / Colder	T _{biv}		°C
Cycling Interval capacity		Cycling Interval efficiency	
for cooling	P _{cycc}		kW
for heating	P _{cych}		kW
Degradation co-efficient cooling**	C _{dc}	0.25	-
Electric power Input in power models other than 'active mode'		Annual electricity consumption	
Off mode	P _{off}	0.001	kW
Standby mode	P _{sb}	0.001	kW
Thermostat-off mode	P _{TO}	0	kW
Crankcase heater mode	P _{CK}	0	kW
Capacity control		Other Items	
Fest	N		
Gestaffelt	N		
Variable	N		
		Sound power level (indoor/outdoor)	L _{WA} 57.0 / 59.0 db(A)
		Global warming potential	GWP 675 kgCO ₂ eq.
		Rated air flow (indoor/outdoor)	- 11.4 / 34.0 m ³ /min
Contact details for obtaining more information		Daikin Europe N.V. Zandvoordestraat 300, B-8400 Oostende, Belgium	

* for staged capacity units, two values divided by a slash (/) will be declared in each box in the section 'Declared capacity of the unit' and 'Declared EER/COP' of the unit.

** if default C_d = 0.25 is chosen then (results from) cycling tests are not required. Otherwise either the heating of cooling cycling test value is required.