

Model HM123HF UB60/ PHCS0 ENCXLEU

Model name	HM123HF UB60/ PHCS0 ENCXLEU
Application	Heating (medium temp)
Units	Indoor, Outdoor
Climate zone (for heating)	n/a
Cooling mode application (optional)	n/a
Any additional heat sources	n/a

General data

Power supply	3x400V 50Hz
Off-peak product	n/a

Outdoor Air/Water**EN 14511-4 | Heating**

Shutting off the heat transfer medium flow passed

Complete power supply failure	passed
Defrost test	passed
Starting and operating test	passed

EN 14511-2 | Heating

	Low temperature	Medium temperature
Heat output	12.00 kW	10.00 kW
El input	2.55 kW	3.23 kW
COP	4.70	3.10

EN 12102-1 | Average Climate

	Low temperature	Medium temperature
Sound power level indoor	0 dB(A)	0 dB(A)
Sound power level outdoor	49 dB(A)	49 dB(A)

EN 14825 | Average Climate

	Low temperature	Medium temperature
η_s	215 %	156 %
Prated	10.00 kW	10.00 kW
SCOP	5.45	3.97
Tbiv	-10 °C	-10 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	8.90 kW	8.90 kW
COP Tj = -7°C	3.54	2.54
Cdh Tj = -7 °C	0.900	0.900
Pdh Tj = +2°C	5.40 kW	5.40 kW
COP Tj = +2°C	5.17	3.92
Cdh Tj = +2 °C	0.900	0.900
Pdh Tj = +7°C	3.50 kW	3.50 kW

COP Tj = +7°C	7.37	5.22
Cdh Tj = +7 °C	0.900	0.900
Pdh Tj = 12°C	3.60 kW	3.60 kW
COP Tj = 12°C	9.24	5.58
Cdh Tj = +12 °C	0.900	0.900
Pdh Tj = Tbiv	10.00 kW	10.00 kW
COP Tj = Tbiv	3.21	2.36
Pdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	10.00 kW	10.00 kW
COP Tj = TOL or COP Tj = Tdesignh if TOL < Tdesignh	3.21	2.36
Cdh Tj = TOL or Pdh Tj = Tdesignh if TOL < Tdesignh	0.900	0.900
WTOL	75 °C	75 °C
Poff	10 W	10 W
PTO	30 W	30 W
PSB	10 W	10 W
PCK	0 W	0 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.00 kW	0.00 kW
Annual energy consumption Qhe	3789 kWh	5211 kWh